

ST-9S+

Arc Fusion Splicer

STI
Innovative Products & Solutions

Features

- * 6-Motors Accurate Core to Core Alignment System
- * 5" High Resolution Display with Touch Panel
- * Largest Battery, 400 Splice & Heat cycles
- * Best Optical System, 400X Magnification
- * Auto Fiber Types Identification & High Accuracy
- * Fastest, 6 Seconds Splice & 18 Seconds Heat Time
- * Touch Panel & Direct Keypad, Dual Operation
- * Dust, Water, Shock/Vibration Resistant, IP52 Certified
- * Light Weight, Compact & User Friendly
- * Industrial Quad-Core CPU with 30% Power Saving
- * Automatic & Real-time ARC Calibration
- * Sensor & Gear-Less Design for Long Life
- * Strongest Built Quality, Metallic Core Assembly



**ECONOMIC
FUNCTIONAL
CONVENIENT
RELIABLE**

Accurate Core to Core Alignment Arc Fusion Splicer

ST-9S+

Arc Fusion Splicer



Accurate Core to Core Alignment Arc Fusion Splicer

Specifications	
Alignment Method	6-Motors Core to Core Alignment (PAS)
Applicable Fiber	SMF(G.652/G.657), MMF(G.651), DSF(G.653), NZDSF(G.655)
Cladding Diameter	80~150um
Coating Diameter	160~3000um
Cleaved Length	5~16mm (Coating diameter<250um), 16mm(Coating diameter>250um)
Typical Splice Loss	SMF: 0.02dB, MMF: 0.01dB, DSF: 0.04dB, NZDSF: 0.04dB
Return Loss	>>60dB
Splice Mode	40 Modes
Operation Mode	Manual / Auto
Auto Heating	Available
Splicing Time	6~12 Seconds
Heating Time	18~26 Seconds for 60mm & 40mm Splice Protection Sleeves
Fiber Magnification	400X (X or Y View), 200X (X and Y View)
Viewing Display	Dual High Sensitivity Camera, 5" HD Color LCD Touch Screen
Data Storage	50000 Fusion Records, 100 Fusion Images
Loss Evaluation	Accurate Loss Estimation using Fiber Core Image & Data Evaluation
Tension Test	1.8~2.25N
Operation Interface	GUI Menu for Easy Operation with Direct Keys or Touch Screen
Battery Capacity	6800mAh, 400 Cycles Splicing & Heating, Charging Time: 3~4 Hours
Power Supply	Adapter, Input: AC100~240V(50/60Hz), Output: DC11~13.5V
Electrodes Life	5000 ARC Discharges, Easy to Replace
External Interface	USB 2.0 Port for Software Upgrading & Splice Results Transfer
Operating Conditions	Temperature: -10°C ~ +50°C, Humidity: 0 ~ 95%
	Altitude: 0 ~ 5000m, Wind: Max. 15m/s
Weight / Size	2.37kg(With battery) / 155mm(L) * 144mm(W) * 155mm(H)



SWAMINARAYAN TECHNOLOGIES INDIA

Office: 603, Ansal Chamber-II, 6, Bhikaji Cama Place
 New Delhi - 110066, INDIA, Phone: +91-11-40563575
 Mobile: +919811486186, E-mail: stechnologies.in@gmail.com
 Web: www.swaminarayantechnologies.com

Service Centre: R-5 & 6, Ansal Chamber-II, 6, Bhikaji Cama Place
 New Delhi - 110066